



Features

- ASK tooling systems are suitable for high speed and high precision cutting.
- Special nut design provides better cutting condition and reducing cutting vibration.
- ASK collet can be achieve the best cutting condition when using AA grade.
- Wrench and Stop Screw must be ordered separately.
- Balancing: 30,000 r.p.m G2.5
- ASK 系列適用於高轉速、高精密切削加工，切削效果佳
- 螺帽獨特設計可降低高轉速切削時的風阻及噪音並提升工作效能
- 欲達到切削效果佳，可搭配使用 AA 級筒夾
- ASK 扳手及止付螺絲為另購品
- 動平衡：30,000 r.p.m G2.5



| Model No. | Clamping Range (d) | D | L | L1 | Weight (kg) |
|--------------------|--------------------|----|-------|-------|-------------|
| SK30 ASK06-060 | 2~6 | 20 | 60 | 35.9 | 0.60 |
| ASK10-070 | 2~10 | 27 | 70 | 50.9 | 0.70 |
| -090 | 2~10 | 27 | 90 | 75.9 | 0.80 |
| ASK16-060 | 3~16 | 40 | 60 | 40.9 | 0.90 |
| -090 | 3~16 | 40 | 90 | 65.9 | 1.00 |
| -120 | 3~16 | 40 | 120 | 80.9 | 1.10 |
| ASK20-060 | 4~20 | 48 | 60 | 40.9 | 0.80 |
| ASK25-085 | 6~25.4 | 54 | 85 | 65.9 | 1.20 |
| SK40 ASK06-080/090 | 2~6 | 20 | 80/90 | 60.9 | 1.10/1.20 |
| -100 | 2~6 | 20 | 100 | 80.9 | 1.30 |
| ASK10-080/090 | 2~10 | 27 | 80/90 | 60.9 | 1.20/1.30 |
| -100 | 2~10 | 27 | 100 | 80.9 | 1.40 |
| ASK13-080 | 3~13 | 33 | 80 | 60.9 | 1.30 |
| -100 | 3~13 | 33 | 100 | 80.9 | 1.50 |
| ASK16-080 | 3~16 | 40 | 80 | 60.9 | 1.40 |
| -100 | 3~16 | 40 | 100 | 80.9 | 1.50 |
| ASK20-090 | 4~20 | 48 | 90 | 70.9 | 1.80 |
| ASK25-095 | 6~25.4 | 54 | 95 | 75.9 | 1.90 |
| -110 | 6~25.4 | 54 | 110 | 90.9 | 2.00 |
| SK50 ASK06-100 | 2~6 | 20 | 100 | 80.9 | 3.00 |
| ASK10-100 | 2~10 | 27 | 100 | 80.9 | 3.30 |
| -130 | 2~10 | 27 | 130 | 110.9 | 3.40 |
| -150 | 2~10 | 27 | 150 | 130.9 | 3.50 |
| ASK13-100 | 3~13 | 33 | 100 | 80.9 | 4.50 |
| -130 | 3~13 | 33 | 130 | 110.9 | 4.70 |
| -150 | 3~13 | 33 | 150 | 130.9 | 4.90 |
| ASK16-100 | 3~16 | 40 | 100 | 80.9 | 3.50 |
| -130 | 3~16 | 40 | 130 | 110.9 | 3.70 |
| -150 | 3~16 | 40 | 150 | 130.9 | 3.90 |
| ASK20-100 | 4~20 | 48 | 100 | 80.9 | 4.60 |
| -130 | 4~20 | 48 | 130 | 110.9 | 5.00 |
| -150 | 4~20 | 48 | 150 | 130.9 | 5.60 |
| ASK25-100 | 6~25.4 | 54 | 100 | 80.9 | 3.80 |
| -130 | 6~25.4 | 54 | 130 | 110.9 | 4.00 |
| -150 | 6~25.4 | 54 | 150 | 130.9 | 4.20 |

Unit: mm