


Tension & Compression Tap Holder



剛性伸縮攻牙本體

TER


BT / NT series

| Model No. | D | L | F1 | F2 | Tapping Range | Collet Type | Weight (kg) |
|------------|----|-----|----|----|---------------|-------------|-------------|
| BT30 TER16 | 28 | 95 | 8 | 8 | M3~M10 | ER16GB | 0.70 |
| TER20 | 34 | 95 | 8 | 8 | M3~M12 | ER20GB | 0.80 |
| BT40 TER16 | 28 | 85 | 8 | 8 | M3~M10 | ER16GB | 1.20 |
| TER20 | 34 | 90 | 8 | 8 | M3~M12 | ER20GB | 1.30 |
| TER25 | 42 | 100 | 8 | 8 | M4~M16 | ER25GB | 1.60 |
| TER32 | 50 | 105 | 8 | 8 | M4~M22 | ER32GB | 1.70 |
| TER40 | 63 | 125 | 8 | 8 | M6~M30 | ER40GB | 2.60 |
| BT50 TER16 | 28 | 95 | 8 | 8 | M3~M10 | ER16GB | 3.90 |
| TER20 | 34 | 95 | 8 | 8 | M3~M12 | ER20GB | 4.00 |
| TER25 | 42 | 105 | 8 | 8 | M4~M16 | ER25GB | 4.20 |
| TER32 | 50 | 105 | 8 | 8 | M4~M22 | ER32GB | 4.30 |
| TER40 | 63 | 120 | 8 | 8 | M6~M30 | ER40GB | 4.90 |

Unit: mm



- TER tap holder uses the ER-GB tap collet and easy to get.
- The nut could not be over tightening to avoid damaging the body and nut.
- Wrench must be ordered separately.
- TER 伸縮攻牙本體須搭配 ER-GB 攻牙筒夾做使用
- 使用時，螺帽請勿過度鎖緊以免造成本體及螺帽損壞
- ER 扳手為另購品




Straight Shank

直柄剛性伸縮攻牙本體

| Model No. | D | L | L1 | F1 | F2 | Tapping Range | Collet Type | Weight (kg) |
|-----------|----|----|----|----|----|---------------|-------------|-------------|
| C20 TER16 | 28 | 75 | 55 | 5 | 12 | M3~M10 | ER16GB | 0.40 |
| TER20 | 34 | 80 | 55 | 5 | 12 | M3~M12 | ER20GB | 0.50 |
| TER25 | 42 | 80 | 55 | 5 | 12 | M4~M16 | ER25GB | 0.80 |
| C25 TER16 | 28 | 75 | 65 | 5 | 12 | M3~M10 | ER16GB | 0.50 |
| TER20 | 34 | 80 | 65 | 5 | 12 | M3~M12 | ER20GB | 0.60 |
| TER25 | 42 | 80 | 65 | 5 | 12 | M4~M16 | ER25GB | 0.90 |
| TER32 | 50 | 80 | 65 | 5 | 8 | M4~M22 | ER32GB | 1.10 |
| C32 TER16 | 28 | 75 | 70 | 5 | 12 | M3~M10 | ER16GB | 0.70 |
| TER20 | 34 | 80 | 70 | 5 | 12 | M3~M12 | ER20GB | 0.80 |
| TER25 | 42 | 80 | 70 | 5 | 12 | M4~M16 | ER25GB | 1.00 |
| TER32 | 50 | 80 | 70 | 5 | 8 | M4~M22 | ER32GB | 1.20 |
| C40 TER16 | 28 | 75 | 70 | 5 | 12 | M3~M10 | ER16GB | 1.00 |
| TER20 | 34 | 80 | 70 | 5 | 12 | M3~M12 | ER20GB | 1.00 |
| TER25 | 42 | 80 | 70 | 5 | 12 | M4~M16 | ER25GB | 1.20 |
| TER32 | 50 | 80 | 70 | 5 | 8 | M4~M22 | ER32GB | 1.50 |

Unit: mm



- TER tap holder uses the ER-GB tap collet and easy to get.
- The nut could not be over tightening to avoid damaging the body and nut.
- Straight shank tap holder also has flat shank type to choice. When ordering, please specify "FLAT".
- Wrench must be ordered separately.
- TER 伸縮攻牙本體須搭配 ER-GB 攻牙筒夾做使用
- 使用時，螺帽請勿過度鎖緊以免造成本體及螺帽損壞
- 另有直柄削平面可供選購，請於訂購時註明 "削平面"
- ER 扳手為另購品



P12- ER Nut

P16-ER GB Collet

P13- Wrench